

RECLAMATION

Managing Water in the West


Revitalization of Rivers in the United States Using Dam Removal

**Tim Randle, M.S., P.E., D.WRE.
Manager, Sedimentation and
River Hydraulics Group**



U.S. Department of the Interior
Bureau of Reclamation

Dams come in a variety of sizes, they serve a variety of purposes, and they have a variety of impacts.



Glen Canyon Dam impounds the Colorado River near the border between Arizona and Utah



RECLAMATION


Benefits of Dams to Society

- Storage and diversion of water for agriculture, municipal, and industrial use
- Flood control
- Hydropower
- Navigation
- Lake recreation (boating, fishing, swimming)
- Sediment retention

Impacts of Dams on Streams

- Altered stream flow patterns and temperature (net reductions in stream flow)
- Decreased oxygen levels
- Blocked migration of fish and other aquatic organisms (turbines hurt fish and increase risk of predation)
- Trapping of sediment, debris, and nutrients

History of U.S. Dam Construction



Nearly
81,000
major
dams in
the United
States
(2005)



RECLAMATION

Over 750 dams removed in the United States

- Mostly small dams removed
- Mostly in the states of Pennsylvania, Ohio, Wisconsin, and California
 - Also in the states of Rhode Island, Tennessee, Illinois, and Washington

Reasons for Dam Removal


- Provide for fish and boat passage
- Revitalize rivers and their ecosystems
- Eliminate safety hazards and liability

Common Factor

- In nearly all dam removal cases, the original purpose of the dam was no longer being served or the present function of the dam could be met through other means.

RECLAMATION

History of U.S. Dam Removal



RECLAMATION

U.S. Dam Removal Science Initiative

- Heinz Center for Science, Economics and the Environment
 - Dam Removal: Science and Decision Making (2002)
 - Dam Removal Research Status and Prospects (2003)

U.S. Dam Removal Guidelines

- American Society of Civil Engineers
 - Guidelines for Dam Decommissioning (1997)
 - Monograph on Sediment Dynamics upon Dam Removal (2010)
- Aspen Institute (Policy Guideline)
 - Dam Removal - A New Option For a New Century (2002)

U.S. Dam Removal Guidelines

- U.S. Society on Dams
 - Guidelines for Dam Decommissioning Projects (2011)
- U.S. Subcommittee on Sedimentation
 - Dam Removal Analysis Guidelines for Sediment (2011)

U.S. Dam Removal Initiatives

- State initiatives
 - Pennsylvania Fish and Boat Commission
 - Wisconsin Department of Natural Resources
- American Rivers (non-profit organization)
 - Technical advice and support for dam removals
- University of California at Berkeley
 - Clearing House for Dam Removal (website)

Dam Removal Challenges


- Political support
 - loss or replacement of project benefits
- Funding
- Structural integrity during removal
- Diversion and care of stream
- Reservoir sedimentation and downstream impacts to water quality and morphology
- Uncertainty

RECLAMATION

Dam Removal Considerations

- Partial or complete dam removal
- Timing and rate of dam removal
- Stream diversion through, over, or around the dam during its removal
- Sediment erosion or removal
- Flood considerations
 - Structural stability during removal
 - Avoidance of downstream flood waves

Why should reservoir sediment be considered?



RECLAMATION

Potential Sediment Issues


- Reservoir restoration (veg & topo)
- Temporary increase in suspended sediment concentration and turbidity
- Riverbed aggradation, channel adjustments, and increased flood stage
- Sedimentation at water intakes
- Finer bed-material grain size
- Growth in coastal or lake delta

RECLAMATION

Reservoir Sediment Management Alternatives



- River Erosion
- Mechanical Removal
- Reservoir Stabilization



RECLAMATION

River Erosion

- River is allowed to erode a channel through the reservoir sediments
- The rate of erosion depends on the rate of reservoir drawdown
- Most commonly adopted alternative
- Least cost, but maximum turbidity

RECLAMATION


Mechanical Removal



- Sediments are removed from the reservoir
- Options include:
 - Hydraulic dredge and slurry pipeline
 - Mechanical excavation and truck transport
- High cost, but prevents sediment from entering the downstream river channel.


RECLAMATION

Reservoir Stabilization



RECLAMATION

When is reservoir sediment a problem?




RECLAMATION

Reservoir Sediment Impact Indicators

- 1. Reservoir size relative to mean annual river flow**
- 2. Reservoir level fluctuations**
- 3. Reservoir sediment volume relative to the annual sediment transport capacity of the downstream channel**
- 4. Concentration of contaminants relative to background levels**

Reservoir Sediment Trap Efficiency

$$K = SI \text{ (sedimentation index)} \times g \text{ (gravitational acceleration)}$$



Ratio of reservoir size to mean annual inflow

Case Studies

Elwha and Glines

Canyon Dams, WA

Chiloquin Dam, OR

Grants Pass, OR

Chiloquin, OR

Savage Rapids Dam, OR

United States of
America

© 2010 Europa Technologies

© 2010 Google

© 2010 Tele Atlas

US Dept of State Geographer

40°01'32.58" N 98°46'02.19" W elev 1864 ft

Eye alt 2842.72 mi

RECLAMATION


Chiloquin Dam on the Sprague River, Oregon (1.4 km)

- Constructed in 1914 by U.S. Indian Service for irrigation.
- Concrete diversion dam
 - 3.4 m high
 - 64 m long
- Reservoir pool
 - 70,000 m³

RECLAMATION

Endangered Fish

- Lost River sucker *Deltistes luxatus*



- shortnose sucker *Chasmistes brevirostris*



RECLAMATION

Project Goals

- Remove dam to restore fish passage and eliminate structural safety concern
- Provide water to irrigation district
 - Pumping plant constructed
- Avoid downstream sediment impacts to
 - Pumping plant
 - Aquatic environment

RECLAMATION


Chiloquin Reservoir

1. Relative reservoir size: 0.00014
2. No reservoir pool fluctuation
3. Sediment volume equivalent to: < 1 year sediment load (39 % silt and clay)
4. No contaminants above background levels

SMALL SEDIMENT PROBLEM

RECLAMATION

Chiloquin Dam, July 2008



RECLAMATION

Chiloquin Dam, August 2008



RECLAMATION

Chiloquin Dam, August 2008



RECLAMATION

Chiloquin Dam, August 2008

- Only a small amount of sediment
- 1,600 submerged logs cut from trees
- Low flows following dam removal
- Total project cost of \$20 million for dam removal and pumping plant construction

08/19/2008

RECLAMATION

Savage Rapids Dam

Rogue River, Oregon (173.2 km)

- Built in 1921 by the Grants Pass Irrigation District to divert water for irrigation
- Rehabilitated by the U.S. Bureau of Reclamation during the 1960's

4. 8. 2002 09:14

RECLAMATION

Savage Rapids Dam

Rogue River, Oregon (173.2 km)

- Concrete diversion dam
 - 9.1 to 12.4 m high
 - 140 m long
- Reservoir pool
 - 0.8 km to 4.1 km long
 - 370,000 m³

4. 8. 2002 09:14

RECLAMATION

Savage Rapids Project Goals

- Remove dam to restore fish passage
 - Salmon and trout
- Provide water to irrigation canals along both sides of the river
 - Construct pumping plant
- Avoid downstream sediment impacts to
 - Pumping plant
 - Municipal water intake
 - Aquatic environment

RECLAMATION



Savage Rapids Dam

- New pumping plant and pipe bridge were constructed prior to dam removal

RECLAMATION


Savage Rapids Reservoir

1. Relative reservoir size: 0.0001
2. Reservoir elevation seasonally fluctuates 3.4 m
3. Coarse sediment volume equivalent to: 1 to 2 year sediment load (2 % silt and clay)
4. No contaminants above background levels

MODERATE SEDIMENT PROBLEM

RECLAMATION

Savage Rapids Dam, April 2009



RECLAMATION



RECLAMATION



RECLAMATION



RECLAMATION



RECLAMATION

Pilot Channel Excavation



RECLAMATION



RECLAMATION

Savage Rapids Dam, Sept 2009

- Total Projects Costs: \$40 million
 - \$5 million for dam removal




RECLAMATION



RECLAMATION

Savage Rapids Dam Removal Immediately Downstream of Pilot Channel Right Bank



Savage Rapids Dam Oct 2009




RECLAMATION

Savage Rapids Dam Jan 2010



RECLAMATION



Sediment deposition at
the pumping plant intake
had to be excavated

RECLAMATION

Elwha River, Washington



RECLAMATION



RECLAMATION



RECLAMATION



Elwha Dam (7.9 km)



Glines Canyon Dam
(21.7 km)

Strait of Juan de Fuca



840 km²
100 km of
tributaries

RECLAMATION

Lake Aldwell behind Elwha Dam




- 10 million m³
- 3 km long
- 90 to 600 m wide

RECLAMATION

Elwha Dam and Powerplant

- Constructed in 1913 for hydropower
- 32 m high concrete gravity dam
- 14.8 MW Powerplant
- 7.9 km upstream from river mouth



RECLAMATION



Lake Mills behind Glines Canyon Dam

- 50 million m³
- 3 km long
- 300 to 600 m wide

RECLAMATION

Glines Canyon Dam

- Constructed in 1927 for hydropower
- Concrete arch dam
 - 64 m high
 - 15 to 46 m wide
- 13.3 MW Powerplant
- 21.7 km upstream from river mouth



RECLAMATION

Project Goals

- Remove both Elwha Dams to restore fish passage and ecosystem processes (100 km of river and tributaries reconnected)
- Continue to provide water for municipal and industrial users
- Continue to provide flood protection

RECLAMATION

Historic Elwha River before the Dams



RECLAMATION



Elwha Watershed



Chinook Salmon
Oncorhynchus tshawytscha

RECLAMATION



Elwha Watershed



Steelhead Trout
Oncorhynchus mykiss


RECLAMATION



Elwha Watershed

Chum Salmon
Oncorhynchus keta

RECLAMATION



Elwha Watershed



Coho Salmon
Oncorhynchus kisutch

RECLAMATION



Lake Sutherland



Elwha Watershed



Sockeye Salmon
Oncorhynchus nerka

RECLAMATION



Elwha Watershed



Bull Trout
Salvelinus confluentus

RECLAMATION




Elwha Watershed



Pink Salmon
Oncorhynchus gorbuscha

RECLAMATION

Potential Range Map for the Seven Elwha Salmonids



RECLAMATION

Lake Mills (Glines Canyon Dam)

1. Relative reservoir size: 0.037
2. Run of the river operation
3. Sediment volume equivalent to:
 - a. 85-year coarse-sediment load
 - b. 60-year fine-sediment load
4. Only iron and magnesium are above background levels

MAJOR SEDIMENT PROBLEM

RECLAMATION

Reservoir Sedimentation



Lake Aldwell



Deltas

Lake Mills

RECLAMATION

Reservoir Sedimentation: 16 million m³

Lake Mills Sediment Volume:

- 13 million m³
- ½ clay and silt
- ½ sand and gravel

Lake Aldwell Sediment Volume:

- 3 million m³
- 2/3 clay and silt
- 1/3 sand and gravel

13 16:02

RECLAMATION

Planning Process

- The National Park Service completed a programmatic Environmental Impact Statement to determine the best way to achieve river restoration.
- The Record of Decision was to remove both dams.

RECLAMATION

Planning Process (continued)

- A second Environmental Impact Statement was completed to determine the best way to remove the dams and manage the reservoir sediment.
- The Record of Decision was to concurrently remove both dams in controlled increments and allow the Elwha River to erode a portion of the sediments from both reservoirs.

Dam Removal and Sediment Management Plan

- Beginning in late 2011, concurrently remove Elwha and Glines Canyon Dams over a two and three-year period.
- This rate is considered fast enough to limit impacts to a few year classes of fish, but slow enough that downstream impacts can be tolerated.



Fish Windows

Dam removal and reservoir drawdown will be temporarily halted during fish window time periods:

May - June, Aug - Sep, Nov - Dec

RECLAMATION

Sediment Management Plan (continued)

- The Elwha River will be allowed to erode and redistribute the sediments within each reservoir. A portion of the reservoir sediments will be eroded to the sea.
- Adaptive Management will be applied to insure impacts do not exceed the capacity of mitigation measures.


Sediment Management Plan (continued)

- The following infrastructure is being built to mitigate project impacts:
 - A diversion weir and engineered riffle provide river water for industrial and municipal use and allow fish passage. This facility replaces the old rock diversion dam, which had fish passage problems.
 - Water treatment plant near the river will pre-treat diverted water for existing water users.

New Diversion Weir



RECLAMATION





Elwha Water Treatment Plant

Sediment Management Plan (continued)


- Infrastructure (continued):

- Municipal water treatment plant.
- Industrial water treatment plant.
- Flood protection structures:

- increased height of existing levees and
- new levees and dikes




RECLAMATION



**Glines Canyon
Dam
Elwha River, WA**

RECLAMATION

Glines Canyon Dam Removal





Glines Canyon Dam Removal

RECLAMATION

Project Costs

- Total Project Costs: \$200,000 million
 - \$20,000 for the removal of both dams



RECLAMATION



Elwha Dam Removal

(Artist Rendition)

RECLAMATION

Sediment Impact Predictions are Based on Several Investigations

- 1994 Lake Mills Drawdown Experiment
- Reservoir sediment erosion models:
 - Numerical model
 - Physical model
- Downstream sediment transport numerical model (HEC-6)
- Monitoring



1994 Lake Mills Drawdown Experiment




6 m over 1 week
constant for 1 week

RECLAMATION

Drawdown Test Measurements

- Stream gaging of discharge, suspended load, and bedload
- Repeat cross-section measurements
- Time lapsed photography
- Aerial photography
- Bed material size measurements and mapping



RECLAMATION

Lower Delta

4/09/94 4:02 pm, 179.5 m, 33.7 m³/s, 5 mg/L Q_s 9 16:02

RECLAMATION

Lower Delta



4/10/94 8:02 am, 178.9 m, 30.9 m³/s

RECLAMATION

Lower Delta



04/11/94 8:02 am, 178.0 m, 29.4 m³/s

11 8:02

RECLAMATION

Lower Delta

04/12/94 8:02 am, 177.1 m, 30.3 m³/s

12 8:02

RECLAMATION

Lower Delta

4/13/94 8:02 am, 176.2 m, 28.6 m³/s, 2,010 mg/L Q_s

RECLAMATION

Lower Delta



4/14/94 8:02 am 175.3 m, 26.4 m³/s, 1,990 mg/L Q_s

RECLAMATION

Lower Delta

4/15/94 12:46 pm, 174.6 m, 25.2 m³/s, 2,200 mg/L Q_s

RECLAMATION

Lower Delta

4/16/94 12:46 pm, 174.3 m, 26.3 m³/s, 5,210 mg/L Q_s

RECLAMATION

Lower Delta



17 12:46

4/17/94 12:46 pm, 174.3 m, 32.6 m³/s

RECLAMATION

Lower Delta

4/18/94 12:46 pm, 572.0 m, 41.9 m³/s, 1,720 mg/L Q_s

RECLAMATION

Lower Delta



4/19/94 12:46 pm, 572.0 m, 49.8 m³/s

RECLAMATION

Lower Delta

4/20/94 12:46 pm, 174.3 m, 43.6 m³/s, 1,555 mg/L Q_s

RECLAMATION

Lower Delta

4/23/94 10:31 am, 174.3 m, 36.8 m³/s

23 10:31

RECLAMATION

What did we learn?

- Erosion of the delta was very rapid, even during low river flow.
- The armor layer was mobilized by head-cut erosion.
- Both vertical incision and lateral erosion processes were very important.
- The eroding delta sediments completely re-deposited across the width of the receded reservoir.

RECLAMATION

Horizontal scale = 1 : 310

3.36 km = 10.8 m

**University of
Minnesota
Saint Anthony
Falls Laboratory**

Chris Bromley

University of Nottingham / Oregon State University

Horizontal scale = 1 : 310

1,070 m = 3.5 m

**University of
Minnesota**

**Saint Anthony
Falls Laboratory**

Chris Bromley

University of Nottingham / Oregon State University

Lake Mills Physical Model Experiment

Chris Bromley
University of
Nottingham / Oregon
State University





0 of 21

RECLAMATION



3 of 21

RECLAMATION



6 of 21

RECLAMATION



9 of 21

RECLAMATION



12 of 21

RECLAMATION



15 of 21

RECLAMATION



18 of 21

RECLAMATION




21 of 21

RECLAMATION



TION

Erosion Along Delta Margin



Erosion Along the Delta Margin

- Very unnatural landscape
- Potential for significant delta erosion after dam removal
- Different result than numerical model



RECLAMATION

Erosion Along Center Pilot Channel



Erosion Along Center Pilot Channel



Erosion Along Center Pilot Channel

- More natural landscape
- Remaining sediments left in more stable condition
- Model results are very similar to numerical model



RECLAMATION

Predicted Reservoir Sediment Erosion

- Erode $\frac{1}{4}$ to $\frac{1}{3}$ of coarse reservoir sediment
 - 400,000 to 600,000 m³ of gravel
 - 1,300,000 to 1,800,000 m³ of sand
- Erode $\frac{1}{2}$ to $\frac{2}{3}$ of fine sediment
 - 4,000,000 to 5,000,000 m³ of silt and clay

Predicted Downstream Fine Sediment Transport


- Largest peak suspended-sediment concentrations are expected to be between 10,000 and 40,000 ppm
- Turbidity is expected to exceed water quality standards (greater than 5 NTU's or 10% more than natural upstream turbidity) during $\frac{3}{4}$ of the dam removal period

Predicted Downstream Channel Changes


- Temporary sediment deposition in river pools
- Straightening of sinuous river alignment
- Aggradation of some riffles
- Temporary braided river channel and channel widening
- Aggradation of sand and gravel could increase 100-year flood stage by up to 1 m

RECLAMATION

2001



RECLAMATION



RECLAMATION

Adaptive Management

- Real-time monitoring to determine if actual sediment impacts agree with predictions and if new water treatment plants and flood control levee modifications can accommodate those impacts.
- Corrective actions can include:
 - More frequent and detailed monitoring
 - Local treatment of bank erosion problems
 - Slower rate of dam removal
 - Temporary halt of dam removal

RECLAMATION

Real-Time Monitoring

- Reservoir sediment erosion and redistribution
- Reservoir hillslope stability
- Stream gaging of discharge, turbidity, suspended-sediment concentration, and bedload
- Riverbed aggradation and flood stage
- Aquifer characteristics
 - water table and well yields
- River channel planform and geometry
- Large woody debris
- Web cameras

RECLAMATION

Possible WEB Camera Views



Lake Mills Delta



Lower Lake Mills



Glines Canyon Dam



Lake Aldwell Delta



Lower Lake Aldwell



Elwha Dam

Conclusions

- The policy decision to remove a dam is based on the need for action, stakeholder input, technical information, and available funding.
- Technical information needs to consider removal of the structure, alternative ways of meeting remaining purposes of the dam, sediment management, and mitigation for impacts.

Conclusions (continued)

- The level of sediment investigations can be scaled to the ratio of the reservoir sediment volume to the annual sediment transport capacity of the downstream channel.

A scenic photograph of a river flowing through a lush, forested landscape. The river is surrounded by dense green trees and vegetation. In the background, there are mountains under a clear sky. The river itself is a mix of white water rapids and calmer sections. A large log lies across the river in the foreground. The overall scene is peaceful and natural.

Thank you
Obrigado!

RECLAMATION